

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2004-175121

(43)Date of publication of application : 24.06.2004

(51)Int.CI.

B60R 21/20

(21)Application number : 2002-313176

(71)Applicant : MITSUBOSHI BELTING LTD

(22)Date of filing : 28.10.2002

(72)Inventor : KURIMOTO TAKUYA
ONO TOSHIYUKI
TAKENAKA AKIRA
FUJITA MASAHIWA

(30)Priority


Priority number : 2002284760 Priority date : 30.09.2002 Priority country : JP

(54) AIRBAG DOOR-INTEGRATED INSTRUMENT PANEL AND ITS MANUFACTURING METHOD

(57)Abstract:

PROBLEM TO BE SOLVED: To provide an instrument panel which includes an airbag door part of which the tear line is invisible from a cabin, and in which the airbag door is cleaved without splashing because the airbag door is bent along a hinge line in cleavage, and which is completely torn along the tear line.

SOLUTION: In this airbag door-integrated instrument panel and its manufacturing method, intermittent holes 7 are formed in a broken line by laser beam machining from a back side of the instrument panel 1 in the tear line 4, and the holes 7 passes through the core material 9 and reaches surface material. A stepped groove 15 is formed by the laser beam machining from the back side of the instrument panel 1 in a hinge part 16, and the stepped groove 15 does not pass through the core material 9.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]